

## 4G LTE Alarm.com hybrid alarm system















- VESTA hybrid control panel with 4G LTE Alarm.com
- Incorporates via F1 868Mhz radio, WiFi, IP, Z-Wave and ZigBee
- 16 expandable wired zones
- Up to 160 zones in total (wired and wireless)
- 2 partitions and 80 users
- 1 PGM output (Siren)
- Up to 32 VESTA-114 keypads
- Configuration by smarthomesec APP
- Grade 3 certified.



Reference / Model	VESTA-405 / ADC Hybrid
Alarm.com 4G (LTE) model	
Amplified fast connection for external GPRS antenna (not include recommended)	led, VESTA-275 or VESTA-276
Advanced automation and home automation management feat	cures
Built-in F1 868Mhz radio compatible with all F1 devices in the ca	italog (2 km in open field)
Incorporates Z-Wave 800 module	
Incorporates ZigBee 3.0 module	
Built-in IP module	
Built-in WiFi IEEE802.11 a/b/g/n/ac, at 2.4GHz/5Ghz	
Built-in 4G LTe alarm.com module(only compatible with Aları	m.com)
4G LTE frequencies: B1 (2100 MHz), B3 (1800 MHz), B5 (850 MH MHz)	lz), B7 (2600 MHz), B8 (900 MHz), B20 (800
Allows up to 16 wired zones on board expandable by zone expa	nders
Allows both wired and F1 radio zones (160 zones in total)	



## 4G LTE Alarm.com hybrid alarm system

Reference / Model	VESTA-405 / ADC Hybrid
2 security areas (expandable to 8)	
Allows up to 32 <b>VESTA-114</b> wired keypads (KP-35-COMBO)	
Up to 80 users (40 per area)	
1 siren output and 1 PGM output (400 mA)	
Full programming in less than 10 minutes from web and SmartHor	meSec app
Flexibility of wiring and selection of resistance values for each zone	е
Integration with DAHUA IP cameras	
Compatibility with all F1 devices for automatic control of your insta	allation (relays, sockets, sensors, etc.)
Supports indoor and outdoor PIRCAMS, allowing users and central	stations to visually verify the alarm
Programming of up to 100 automatic rules (automatic watering, p by calendars, auto-arming, etc.).	resence simulation, control of any device
Extreme convenience and flexibility in the methods of communica (MANITOU, encrypted MANITOU, CID, SIA, FTP, HTTP).	tion of events and photos to the ARC
With VESTA's SmartHomeSec application you can remotely contro video surveillance system and the smart devices in your home.	l and manage both your security and
VESTA's hybrid PBX is compatible with Google Home and Alexa	
Integration with Fibaro automatic devices (Fibaro Dimmer 2, Roller 2)	Shutter 3, Smart Module, Single Switch
RJ45 network interface	
Tamper tamper cover and wall tamper	
External power supply: 100V ~ 240V AC, 50/60Hz	
Total power consumption: 400 mA (wired zones, auxiliary output a	nd hybrid keypad)
Supports 12V/4A sealed lead-acid back-up battery (not included) w	vith up to 21 hours of battery life
Operating temperature -10°C $\sim$ +45°C (-10°C $\sim$ +45°C)	
Operating relative humidity up to 85% (non-condensing)	
Dimensions: 268 (W) x 320 (H) x 80 mm	
Certified EN50131 Grade 2 (wireless mode) and Grade 3 (wired), C	Class II