

# VESTA-410

VST-892-AMX

## PIRCAM VGA detector for indoor use



- PIRCAM Vesta indoor detector
- PIR coverage of 12 meters, 90°
- Two sensitivity levels
- 102° optics, IR illumination of 7 meters
- VGA resolution
- Anti-masking function
- Anti-pet 25 kg



### Reference / Model

**VESTA-410 / VST-892-AMX**

Detection range of 12 meters, 90°.

Advanced dynamic speed adjustment algorithms to adapt image transfer rate to signal quality

Anti-pet up to 25 kg with remote activation/deactivation

Anti-masking function to detect any attempt to blind the detector

Two adjustable sensitivity levels: High / Normal

VGA CMOS sensor camera

Resolution: 640x480, 320x240

Camera viewing angle of 102°.

Infrared illumination up to 7 meters

Three alarm image processing options: 640x480@3ips, 320x240@3ips and 320x240@6ips

Adopts SF1 technology, which makes transferring alarm images even faster than with its predecessors

Periodic monitoring signals

Tamper protection to prevent unauthorized sabotage

# VESTA-410

VST-892-AMX



## PIRCAM VGA detector for indoor use

Reference / Model	VESTA-410 / VST-892-AMX
	Suitable for security and home automation
	RF frequency: 868MHz
	Power supply: 3 x CR123A 3V lithium batteries
	Battery life up to 9 years
	Operating temperature from -10°C ~ +45°C
	Relative humidity up to 85% (non-condensing)
	Installation height of 2.3 ~ 2.5 meters (8 ~ 8.5 feet)
	Wall or corner installation (swivel mount required)
	Swivel angles of optional swivel mount: 80°(H), 70°(V)
	Dimensions: 72(W) x 138(H) x 47.2 mm